

ZKAIO2000

All in One Biometric Smart Pos Terminal



Features

- Power-efficient Intel® Celeron J1900 2.0 GHz Quad-Core processor;
- Optional Intel® Core i3 and i5 processor;
- 15" Bezel-Free True-Flat PCAP touch screen;
- Multiple I/O interfaces for peripherals;
- Standard with 2G RAM and 32G SSD;
- Standard with 8C high-definition digital tube;
- Optional 3 track MSR, attached VFD & 15" customer display;
- Easy Installation and Durable;

Optional



Magnetic Stripe
Card Reader



2nd LCD Display Screen



Barcode Scanner



Mifare/RFID



Thermal Printer



Cash Drawer



VFD Customer Display



Fingerprint

Specifications

Model Name	ZKAIO2000		
System			
Processor	Intel® Celeron J1900 Quad-Core processor (2.0 GHz)	Intel® Core i3-4010U Processor (1.7 GHz)	Intel® Core i5-4200U Processor (1.6 GHz)
System Memory	2GB Standard, DDR3L 1333MHz (Max.8GB)		
Storage Device	32GB Msata SSD Standard,1*2.5" HDD & 2.5" SSD		
OS Supported	Windows 7, Windows 8, Windows 10 IoT Enterprise, POS Ready 7, Linux		
Audio	Realtek ALC662		
Display and Touch			
Type	15" TFT LCD, LED Backlight		
Resolution	1024×768		
Touch Screen	Projected Capacitive Touch Screen		
Customer Display	LED (8C digital tube)		
External I/O Ports			
VGA	1*DB-15		
USB	5*USB 2.0 & 1*USB 3.0	4*USB 2.0 & 2*USB 3.0	4*USB 2.0 & 2*USB 3.0
Serial & HDMI	1*RS232 (Max.4pcs)	1*HDMI & 3*RS232	1*HDMI & 3*RS232
LAN	1*RJ45		
Audio	1*Line-out		
Power			
Power Supply	Adaptor 12V DC 5A		
Physical Environment			
Operating Temperature	0℃ ~ 35℃ at 20% - 80% Humidity		
Storage Temperature	- 20℃ ~ 55℃ at 20% - 80% Humidity		
Dimensions (W*H*D)	358*390*236mm		
Packing Dimensions	460*490*315mm		
Net Weight	6.8kg		
Packing Weight	7.9kg		
Certification	CE FCC		
Color	Silvery		
Options & Peripherals			
2nd Display	15" TFT LCD		
Customer Display	20 Columns × 2 Lines		
MSR	3 Tracks		
Fingerprint	USB fingerprint reader (SLK20R)		



V1.0 2018.06.29

ZKTECO CO.,LTD.

www.zkteco.com

E-mail: sales@zkteco.com



© Copyright 2018 ZKTECO CO., LTD. All rights reserved.