

Datasheet

C317A

Premium touch screen for your home

The C317A multifunctional communicator, with an Android operating system, provides audio and video communication with Door phones via SIP 2.0 protocol. It delivers the ultimate touch screen experience in an unobtrusive, space-saving design featuring a brilliant 10 inch capacitive touch screen display.

At a Glance

- Ultra clear, stylish appearance
- 10" capacitive touch screen with energy saving mode
- Built-in 1MP CMOS camera
- Built-in Wi-Fi (2.4GHz, IEEE802.11 b/g/n)
- Reception of a HD picture from the door communicator
- Two-way communication with other units in the network, based on SIP v2.0 protocol
- Powered by PoE or external source
- Tamper resistant design;

Touch Screen Display

Display Mode: Normally black, Transmissive

LCD Size: 10 inch (Diagonal)

Aspect Ratio: 16:9

Resolution: 1280x800

Contrast ratio: 800:1

Luminance: 350 cd/m²

Viewing Angle: ±89° Left, ±89° Right,
±89° Upper, ±89° Lower

Touch Screen: Projected Capacitive

Camera

Camera: 1MP Camera, CMOS

Audio

Features: Built-in microphone and speaker

Video

Streaming Formats: H.264

Memory

RAM: 2GB

ROM: 8GB



Interface

Ethernet: 2x10/100 Mbps ports, auto-switching, auto-discovery, auto-negotiating, full/half duplex, DHCP, IEEE802.3af compliant

RS485: 1 RS485 port

Alarm: Support 8 channels input

Relay Out: 2 Relay Out (NO/COM/NC)

Bell In: 1 Bell In

Memory Slot: 1 Micro SD slot

Environmental

Temperature: 14° to 112°F (-10° to 45°C)

Humidity: 10% to 90% (non-condensing)

Mechanical parameters

Dimensions (W x H x D): 251 x 182.5 x 22 mm

Application Scenario

Villas

Apartment complexes

Home automation systems

Modern interiors